



### TECHNICAL SPECIFICATIONS

|                        |           |
|------------------------|-----------|
| Overall length L H     | 7.50 m    |
| Inside length          | 6.10 m    |
| Overall width L H      | 3.05 m    |
| Inside width           | 1.90 m    |
| Number of chambers     | 7         |
| Inflation valves       | 7         |
| Buoyancy tube diameter | 0.59 m    |
| Light mass             | 1480 kg   |
| Lightship weight       | 2090 kg   |
| Full load weight       | 3652 kg   |
| Number of people in C  | 18        |
| Neoprene hypalon float | 1670 dTex |

### ENGINE

|                          |           |
|--------------------------|-----------|
| Fuel                     | Petrol    |
| Engine type              | Outboard  |
| Engine shaft             | UltraLong |
| Max engine power         | 350 cv    |
| Recommended engine power | 200 cv    |
| Max engine weight        | 462 kg    |

### TRAILER

|                     |         |
|---------------------|---------|
| Recommended payload | 1800 kg |
|---------------------|---------|

### CONFIGURATION EXAMPLE

- Davit XVPRO
- Front locker
- Deck hatch
- Console C1011
- Bolster seat 1011 XL
- Teck Table
- Box seat S1520
- Roll-bar RB7
- 3 Tubes reinforcements of 0,75 meter on each side
- Interruption of lifeline on tube reinforcement
- Bow stripe